

PROFOUND CARING **BEYOND CLEANING**

Rejuvenates the life of marble,
granite & all flooring surface



STONEK

ABOUT

STONEK

STONEK is an Indian brand, which manufactures and trade chemical products for stone care solutions, which works adequately on Marble, Natural Stones and Granite. Our products are widely used to protect and maintain the floors.

We offer wide range of products designed and developed to polish and rejuvenate the natural appearance of surfaces. The product list comprises of Marble glue, mastics, resins, sealers, joint fillers, polishes, stain removers and cleaners etc.

We make sure that we serve our customers in best possible ways always by updating and enhancing ourself according to today's need and will continue to do so. It's our commitment.



The system in which STONEK
PROTECTS **THE SURFACE**

Stone life increases | Maintaining High Gloss | Uniform floorings | Stain resistant | Procuring cracks and holes

MASTICS

DESCRIPTION: A premium range, Very thin, Polyester resin based glue for filling and gluing any marble or natural stones. Gives a very fine finish to joint Cracks. MASTICS is a fine grade unique product which is used for Joining, & filling medium to large holes in Marble & any kind of Natural stones. It is available in 6 colors in solid & liquid form. The main features of the product are: Fast hardening, Strong binding power & high gloss polish finish.



INSTRUCTION FOR USE: Mix the mastics with hardener in required proportion and apply the mixture by putty blade on the joints, cracks holes (for color matching mix proportionate amount of color pigment). Apply the mix by putty blade within 5-10 minutes of mixing. Allow it to work for 3-4 hours after the application for further polishing steps.

AREA OF USE: Marbles

PACKING AVAILABLE: 1000ml/1.5kg

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

SOLID/FLUID CREAM

DESCRIPTION: STONEK Solid cream and fluid cream is used for joining and filling medium to large holes in marble & any kind of natural stone recommended for beige color marble. STONEK Solid/Fluid cream is a viscosity and surface tension system specially designed for the joint of the marble & granite. It gives a perfect saturation of the surfaces to treat producing a great adhesion of the stone.



INSTRUCTION FOR USE: Mix the mastics with hardener in required proportion and apply the mixture by putty blade on the joints, cracks holes (for color matching mix proportionate amount of color pigment). Apply the mix by putty blade within 5-10 minutes of mixing. Allow it to work for 3-4 hours after the application for further polishing steps.

Area of Use: Marbles

PACKING AVAILABLE: 1000ml/1.5kg

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

SOLID/FLUID WHITE

DESCRIPTION: STONEK Solid white and fluid white is used for joining and filling medium to large holes in marble & any kind of natural stone recommended for light color marble. STONEK Solid/Fluid white is a viscosity and surface tension system specially designed for the joint of the marble & granite. It gives a perfect saturation of the surfaces to treat producing a great adhesion of the stone.



INSTRUCTION FOR USE: Mix the mastics with hardener in required proportion and apply the mixture by putty blade on the joints, cracks holes (for color matching mix proportionate amount of color pigment). Apply the mix by putty blade within 5-10 minutes of mixing. Allow it to work for 3-4 hours after the application for further polishing steps.

Area of Use: Marbles

PACKING AVAILABLE: 1000ml/1.5kg

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

SOLID/FLUID BLACK

DESCRIPTION: STONEK Solid Black and fluid Black is used for joining and filling medium to large holes in marble & any kind of natural stone recommended for black marble & granite. STONEK Solid/Fluid black is a viscosity and surface tension system specially designed for the joint of the marble & granite. It gives a perfect saturation of the surfaces to treat producing a great adhesion of the stone.



INSTRUCTION FOR USE: Mix the mastics with hardener in required proportion and apply the mixture by putty blade on the joints, cracks holes (for color matching mix proportionate amount of color pigment). Apply the mix by putty blade within 5-10 minutes of mixing. Allow it to work for 3-4 hours after the application for further polishing steps.

Area of Use: Marbles

PACKING AVAILABLE: 1000ml/1.5kg

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

SOLID/FLUID TRANSPARENT



DESCRIPTION: STONEK Solid Transparent and fluid Transparent is used for joining and filling medium to large holes in marble & any kind of natural stone recommended for all marble & granite. STONEK Solid/Fluid transparent is a viscosity and surface tension system specially designed for the joint of the marble & granite. It gives a perfect saturation of the surfaces to treat producing a great adhesion of the stone.

INSTRUCTION FOR USE: Mix the mastics with hardener in required proportion and apply the mixture by putty blade on the joints, cracks holes (for color matching mix proportionate amount of color pigment). Apply the mix by putty blade within 5-10 minutes of mixing. Allow it to work for 3-4 hours after the application for further polishing steps.

Area of Use: Marbles

PACKING AVAILABLE: 1000ml/1.5kg

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

SOLID/FLUID CRYSTALLINE



DESCRIPTION: STONEK Solid crystalline and fluid crystalline is used for joining and filling medium to large holes in marble & any kind of natural stone recommended for light color marble. STONEK Solid/Fluid crystalline is a viscosity and surface tension system specially designed for the joint of the marble & granite. It gives a perfect saturation of the surfaces to treat producing a great adhesion of the stone.

INSTRUCTION FOR USE: Mix the mastics with hardener in required proportion and apply the mixture by putty blade on the joints, cracks holes (for color matching mix proportionate amount of color pigment). Apply the mix by putty blade within 5-10 minutes of mixing. Allow it to work for 3-4 hours after the application for further polishing steps.

Area of Use: Marbles

PACKING AVAILABLE: 1000ml/1.5kg

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

RESINO CLEARO

DESCRIPTION: RESINO CLEARO is a water clear resin which is used for joints and filling medium to large holes in marble slabs, stones, travertine. It can be pigmented and turned to any color by adding the polyester pigment. It has strong binding power and fast hardening.



INSTRUCTION FOR USE: Surface must be clean and completely dry. Take required quantity of resin and add hardener. We suggest to use the hardener in a 2% ratio for a proper hardening, Quantity can be changed as per the condition of use. Do not use quantity of hardener higher than 3% or lower than 1%. Mix well the two component parts and apply on the surface. The two components must be mixed accurately to obtain catalytic homogeneity.

Area of Use: Mosaic, Vitrified, Ceramic Tiles, Natural Stone Tiles

PACKING AVAILABLE: 1 Ltr, 5 Ltr, 25 Ltr

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

EPOXY SYSTEM EPOK 1200 (2:1)

DESCRIPTION: Epoxy System EPOK 1200 (2:1) is a dual compound which is transparent and solvent free with low viscosity and self-leveling for strengthening the Marble. It is very stable with respect to atmospheric agent and UV rays and suitable for exterior. It is Ideal for adhesion, sealing, transparency, hardness and smoothing. It is used for filling pin holes and air cracks in the Marble. It enhances the gloss and protect from stains.



INSTRUCTION FOR USE: Take the proportionate amount of Part A & B, mix it well and apply on cleaned grinded surface by putty blade. Allow it to dry for 24 hours and continue with further polishing steps.

AREA OF USE: All kind of Marble & Granite

MIXING RATIO: 100:50

PACKING AVAILABLE: 3 kg set (2kg Component A, 1kg Component B)

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

EPOXY SYSTEM EPOK 8200 (4:1)



DESCRIPTION: Epoxy System EPOK 8200 (4:1) is a dual compound which is transparent and solvent free with low viscosity and self-leveling for strengthening the Marble. It is very stable with respect to atmospheric agent and UV rays and suitable for exterior. It is Ideal for adhesion, sealing, transparency, hardness and smoothing. It is used for filling pin holes and air cracks in the Marble. It enhances the gloss and protect from stains.

INSTRUCTION FOR USE: Take the proportionate amount of Part A & B, mix it well and apply on cleaned grinded surface by putty blade. Allow it to dry for 24 hours and continue with further polishing steps.

AREA OF USE: All kind of Marble & Granite

MIXING RATIO: 100:25

PACKING AVAILABLE: 1.25 kg set (1kg Part A, 0.25kg Part B)

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

HYDRA PROTECK (Top side – water based)



DESCRIPTION: HYDRA PROTECK is anti-stain, oil and water-repellent protecting agent with no color enhancement, reduces the dirt absorption, UV resistant. It is used for water, grease and oil treatment of marble & Granite. It is absorbed by the stone with high degree protection. It is the ideal treatment for all type of stone surface (Polished or grinded or rough), cement, agglomerates, building tiles, bricks, concrete.

INSTRUCTION FOR USE: Surface must be clean and completely dry. Take and apply undiluted product on surface with cotton cloth or paint roller or brush evenly. After 15-20 minutes of application wipe off the excess with an absorbent cloth. Apply twice for the long lasting protection. Do not walk on the treated surface for 24 hours after the treatment.

AREA OF USE: Marble (White)

PACKING AVAILABLE: 1 Ltr

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

NANO SHIELD PROTECK (Top side – Solvent based)



DESCRIPTION: NANO SHIELD PROTECK is solvent based anti-stain, oil and water-repellent protecting agent with no color enhancement, reduces the dirt absorption, UV resistant. It is used for water, grease and oil treatment of marble & Granite. It is absorbed by the stone with high degree protection. It is the ideal treatment for all type of stone surface (Polished or grinded or rough), cement, agglomerates, building tiles, bricks, concrete.

INSTRUCTION FOR USE: Surface must be clean and completely dry. Take and apply undiluted product on surface with cotton cloth or paint roller or brush evenly. After 15-20 minutes of application wipe off the excess with an absorbent cloth. Apply twice for the long lasting protection. Do not walk on the treated surface for 24 hours after the treatment.

AREA OF USE: Marble (White)

PACKING AVAILABLE: 1 Ltr

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

SEAL PROTECK (Back side – water based)



DESCRIPTION: SEAL PROTECK is excellent product suitable as protection sealer against the climbing up stains, with high elasticizing properties. It is formulated with nano silver technology to protect from bacteria and viruses. This product is very effective against increasing humidity and climbing up of stains from support. This product is highly recommended for high porous stones.

INSTRUCTION FOR USE: In order to avoid stains due to salts rise from underside (bottom side of stone): Apply the product on the surface by using brush/roller on the side to lie onto the surface. Once laid it will make a barrier against the rising salts.

AREA OF USE: Used on back side of Marbles, Granites & Natural stones

PACKING AVAILABLE: 5 Ltr

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

WETLOOK PROTECK (Water Repellent Color Enhancer)



DESCRIPTION: WET LOOK PROTECK water based anti-stain, oil and water-repellent protecting agent with color enhancement, reduces the dirt absorption, UV resistant. It is used for water, grease and oil treatment of marble & Granite. It is the premium product to give a heavy protection with a smooth effect by enhancing its natural color for a very long period. It is specially recommended for a very smooth finish for longer period on dark & medium color Marble, Granite & Natural stones.

INSTRUCTION FOR USE: The surface to be treated must be clean, dry, absorbing and free from traces of alien substances. Apply by paint brush and let the material absorb the product according to its natural porosity; rub gently to favor the penetration and to remove eventual excess of product on the surface that anyway no further application is needed, but in case of very absorbing stones a second coat allows the intensification of the wet effect. In any case it is suggested a preliminary test on a small hidden, part of the surface to control, after drying the obtained effect.

AREA OF USE: Marble

PACKING AVAILABLE: 1 Ltr

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

SHINO PROTECK (Color Enhancer)



DESCRIPTION: SHINO PROTECK is the premium product to give a heavy protection with a smooth effect by enhancing its natural color for a very long period. It is specially recommended for a very smooth finish for longer period on dark & medium color Marble, Granite & Natural stones.

INSTRUCTION FOR USE: The surface to be treated must be clean, dry, absorbing and free from traces of alien substances. Apply by paint brush and let the material absorb the product according to its natural porosity; rub gently to favor the penetration and to remove eventual excess of product on the surface that anyway no further application is needed, but in case of very absorbing stones a second coat allows the intensification of the wet effect. In any case it is suggested a preliminary test on a small hidden, part of the surface to control, after drying the obtained effect.

AREA OF USE: Marble & Granite

PACKING AVAILABLE: 1 Ltr

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

CLEANZ PROTECK (Cement Film Remover)



DESCRIPTION: CLEANZ PROTECK has excellent cleaning property with rapid cleaning action of tile, granite & stones. This product is to be used for removing left over cement and concrete from the surface after the laying and fixing process is finished.

INSTRUCTION FOR USE: Apply undiluted/diluted product on surface by using roller or brush and, let the product work and rinse thoroughly with clear water 2 to 3 additional rinsing may be needed to get good result. If required scrub with a hard brush. Rinse the floor with water and use a wet vacuum to cleaned dry the floor.

AREA OF USE: Marble, Granite & Tile

PACKING AVAILABLE: 5 Ltr

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

FLORO CLEANZ (Floor Maintenance Cleaner)



DESCRIPTION: FLORO CLEAN is specially developed for floor maintenance of marble and stones. This product is used for daily floor cleaning and maintenance while maintaining sheen on the stone.

INSTRUCTION FOR USE: Take 3-5 capful in half a bucket of water (3-4 liters). Gently mop the surface & don't rinse. Allow it to dry for 15 minutes.

AREA OF USE: Marble, Granite, Natural Stones & Vitrified Tiles

PACKING AVAILABLE: 1Ltr & 5Ltr

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

MAGICWANDER (Stone Densifier)



DESCRIPTION: MAGICWANDER is water based stone densifier product for protection of marble. Thanks to its high penetration power, It seals over the micro porosity of stone. It increases the hardness and the polish of the marble. It also seals the surface

INSTRUCTION FOR USE: MAGICWANDER is applied on Polished Marble during the polishing process, after the one or two grinding process. Apply a thin coat by wiper and let it dry for 2-3 minutes. Repeat the coating process 15-20 times, according to stone porosity. After completion of coating process wait for 24 hours and continue with next polishing steps.

AREA OF USE: For Marbles, granites, artificial stones & vitrified tiles.

PACKING AVAILABLE: 1 Ltr, 5 Ltr, 25 Ltr

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

NO RUST (Granite Rust Remover)



DESCRIPTION: NO RUST is specifically invented to remove yellowish stains resulting due to oxidation of the elements into the material or into the formation of any kind of material. It should be used to remove yellow rust from all types of granite.

INSTRUCTION FOR USE: Take the required amount of rust remover and a piece of cotton cloth. Pour and rub the rust remover liquid on rusting area with the use of the cotton cloth. As the liquid is formulated to remove the deep rust it needs sunlight treatment. Keep the granite slab under the sunlight to get the good result.

AREA OF USE: Granite

PACKING AVAILABLE: 1 kg, 5 kg, 50kg

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

FF7 EXTRA POLISHING POWDER



DESCRIPTION: FF7 EXTRA powder formulated specifically to create a gloss finish on stone. It is recommended for color marble. It can be used on counter tops and floors. This product gives a crystallize effect on surface.

INSTRUCTION FOR USE: Make sure that the surface is well cleaned and rinsed. Use new pad to get better result. Mix the powder with water and spread on the floor evenly and buff with the machine. Keep the polishing compound wet while refinishing with plenty of water. Refinish area until the desired level of polish has been achieved. Rinse the floor well.

AREA OF USE: Marble and Granite

PACKING AVAILABLE: 1 kg

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

HIGH GLOSSY POLISHING POWDER



DESCRIPTION: HIGH GLOSSY is formulated specifically to create a high gloss finish on stone. This product produces a natural polished finish without changing color of the Marble. This product is used for white and light color marble. It can be used on counter tops and floors. This product gives a crystallize effect on surface.

INSTRUCTION FOR USE: Take Make sure that the surface is well cleaned and rinsed. Use new pad to get better result. Mix the powder with water and spread on the floor evenly and buff with the machine. Keep the polishing compound wet while refinishing with plenty of water. Refinish area until the desired level of polish has been achieved. Rinse the floor well.

AREA OF USE: Marble and Granite

PACKING AVAILABLE: 500 g

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

WAX POLISH



DESCRIPTION: WAX POLISH is a premium product which gives instant effective shine to the marble, granite and natural stones. It's smooth application gives high end performance for long lasting protection to any kind of surfaces.

INSTRUCTION FOR USE: Clean the surface neatly. Apply a thin layer of STONEK Wax Polish with a cloth. Polish gently with a clean cloth before the polish dries. Apply STONEK premium polish daily on the dull surface until required shine is obtained.

AREA OF USE: Marble, Granite & Natural stones

PACKING AVAILABLE: 400g, 1kg

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

EPOK 5185 (White Epoxy Adhesive)



DESCRIPTION: Thixotropic Epoxy Adhesive. Solvent free and perfectly clear to make adhesion in marble & granite. This product has characteristics of strong adhesion, very clear effect in joints, cracks, and holes in marble & granites. The surface to be treated must be clean, dry and free from dust, oils and other subtracts.

INSTRUCTION FOR USE: Take and mix required amount of part A & B, in mixing ratio 2:1. Until blended it well, apply on surface by putty blade. Allow it to dry for 3-4 hours and continue with further process. The two components must be mixed accurately to obtain catalytic homogeneity.

AREA OF USE: Marble & Granite

MIXING RATIO (IN WEIGHT): Component A : Component B = 100:50

PACKING AVAILABLE: 2.25kg set (1.5 kg Component A, 750g Component B)

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

MAX 150 (Stain Remover)



DESCRIPTION: MAX-150 STAIN REMOVER is specifically developed to remove the yellow stains resulting due to reaction of wood, ink and food items on marble floor. It is usually required to remove stains yellow stains on marble near door frames and bathroom.

INSTRUCTION FOR USE: Apply undiluted product on stain area, cover with a transparent plastic sealed by masking tape, and allow it to work for 24 hours. In normal conditions it can be used on polished surface.

AREA OF USE: Marble, Granite, Natural Stones & Vitrified Tiles

PACKING AVAILABLE: 250ml

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.

COLOUR PIGMENT



DESCRIPTION: The easy color system allows any marble worker to obtain the right color to mix with the mastics and epoxy he needs for his own glue, the shade he prefers, totally by doing it himself. Pigments available in all required colors.

PACKING AVAILABLE: 100g, 1kg

STORAGE & SHELF LIFE: Keep the container closed and stored in good ventilated environment, away from direct sunlight for the maximum period 12 months.

SAFETY RULES: Make sure that the application area is enough ventilated. Keep the container closed after usage. Read safety data sheet carefully before use. Always test the product before use.



STONEK

INDIA 

Bangalore

+91 8073291912

contact@stonek.in

www.stonek.in